

CardioResting[™] ECG — we care about you and your patients

Nasiff Associates, Inc. is the **FIRST** and continues to take the lead in PC based Resting ECG ECG Systems. A true 12- lead interpretive ECG solution. Performing fast testing and managing them easily

with you at the point-of-care.

 Performs ECG tests on Windows PC/laptops and devices with USB ports. MAC PC/laptops with Parallels, Boot Camp...

- Cardio Universal EMR Interface™ pdf, bidirectional Dicom, bidirectional HL7 and all standard interfaces...
- Cardio Patient Data Management™ System
- Built-In Networking and unlimited Patient Database
- Legendary quality, excellent customer support and training
- · Reliable, user-friendly, compact and durable devices
- · Feature rich at the best price
- · Advanced security features with password options
- · Made in USA
- FDA Clearance since 1990





Nasiff Cardio Card® PC BASED RESTING ECG SYSTEM

SPECIFICATIONS

CONNECTION WITH PC

TIME BASE

POWER SUPPLY	USB DC 5v
POWER CONSUMPTION	< 200mA from USB
COMPARISONS	ECG/EKG serial historical comparisons
ECG MEASUREMENT RESOLUTIONS	2-4 msec, 1.22uV at 10mm/mV gain
HEART RATE RANGE	30-300bpm
LEADS	Standard 12- lead
LEAD LEAKAGE	< 10uA
ACQUISITION MODE	Simultaneous interpretive 12- lead acquisition
SAMPLING RATE	12- lead sampling rate 250-1000Hz
A/D RATE	1kHz

USB cable connection

DV/MANUE DANIES	5 V	a to the production in
DYNAMIC RANGE	± 5 mV	Official policy (IDC Medical Fig. 2) At 50 TM-2023_81_317_Amr2 Fig. 2) By Company (IDC Medical
FREQUENCY RESPONSE	0.05 to 150 Hz (higher available)	Office during 1912 Spirit aus 24955 of 1965 Shaftering Proposer
GAINS	2.5, 5, 10, 10/5, 20, 40 mm/mV	
INPUT IMPEDANCE	>10 ¹² ohms	Section 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

12.5, 25 and 50 mm/sec

SYSTEM NOISE	<40 uV RTI	Α-
ECC INTEDDDETATION OF ASSES	Mla blocks anlargements axis and AEib	J

FILTERS	AC, baseline, muscle artifact

TIETERO	AO, baseline, muscle a	
CMRR	>120 dB	

NETWORKING	Bu	ilt-in
NETWORKING	Bu	ilt-ir

MEASUREMENTS	HR with global measurements, complete interval values

DIMENSIONS	2.75" W x 1.25" D x 4.87" H (6.985 cm x 3.175 cm x 12.364 cm,
------------	---

WEIGHT	0.26 lb	(0.12 kg)
	0.20 10	0.12 (9)

PC REQUIREMENTS	Tablet/Laptop/Desktop PC, i5 Intel Processor, 8 GB RAM, 256+ GB HD, USB Ports
	MINIDOMIC VD through MINIDOMIC 7 0 11 and MAC's with Doot Comes

WINDOWS XP through WINDOWS 7, 8, 11 and MAC's with Boot Camp, Dual Boot, VMware Fusion or Parallels

WARRANTY Two-year manufacturer's warranty on device and software. Free support and training

ORDERING INFORMATION CardioResting System — CC-ECG1

FOR MORE INFORMATION CONTACT:

Nasiff Associates, Inc. 841-1 County Route 37, Central Square, NY 13036 phone: 315.676.2346 • fax: 315.676.4711 • toll-free: 866.NASIFFA (866.627.4332) tech support: 315.676.2346 • email: sales@nasiff.com • web: www.nasiff.com **CPT CODE 93000** (additional codes: 93005; 93010)



